



FUEL MANAGEMENT  
SYSTEMS



DISPENSERS



KITS



PUMPS



METERS



NOZZLES

# E300

## FEATURES

- HIGH-FLOW PUMP
- STURDY STRUCTURE
- HEAVY DUTY APPLICATION
- IP44

### PERFORMANCE

UP TO  
**300 L/MIN**

FLOW RATE

**AC**  
CONTINUOUS DUTY

POWER

**1,7 BAR**  
MAX

OPERATING PRESSURE



E300



### PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FO0321000	27	59	220X420X330	8,7X16,5X13	1



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

**PIUSI**



ANY BIODIESEL



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN


## CHART



TYPE OF FLUID DIESEL

TEMPERATURE 10°C

## DIMENSIONS



Dimensions expressed in millimeters

## IN THE BOX

- E300 PUMP
- INSTRUCTION MANUAL

## DETAILS



OPEN IMPELLER



2" IN/OUT CONNECTIONS



STEADY SUPPORT

## MATERIALS

- BODY: CAST IRON
- OPEN IMPELLER: CAST IRON
- SEAL: VITON
- SHAFT: STEEL

## TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			RPM	INLET/OUTLET
			L/MIN	GPM	AC VOLT/HZ	POWER WATT	AMP. MAX.		
FO0321000	E 300	D	300	80	230/50	1500	7	2580	2"